

STERILISING CABINETS

OPERATING PRINCIPLE:

The bacteria is sterilised by ultraviolet rays.

HYGIENE:

Sloped top and bottom preventing any retention of water or dust. Ilt is impossible to lay objects on the cabinet. Removable stainless steel rack: it is dishwasher proof and easy cleaning of inside of cabinet.

SAFETY:

The cabinet is fitted with a device to cut out the light when the door is opened: users are not exposed to UV rays. The stop holds the knives of cutter blades, thereby limiting any risks of them falling out and therefore injury



EFFICIENCY:

Thanks to the rack, no part of the knife's blade is in contact with a surface likely to obstruct the efficiency of the rays. The stop is also provided to hold nonmagnetic utensils.

The cabinet is deep enough to allow for cutting disks (up to 157 mm) to be sterilised.



THE RANGE ALSO INCLUDES

■ 20-knife cabinet with grid ref. 806 421

■ 10-knife cabinet with magnetic bar ref. 806 422

All the cabinets are also available with lock and key.

EYE-CATCHING:

The radiused vertical edges give the cabinet a modern edge blending in with the Tournus stainless steel range.







STERILISING CABINETS

TECHNICAL SPECIFICATIONS

ref.806 422

25 avenue Jean Moulir bp 59 71700 Tournus - France

France:

Tel : 03 85 27 42 42 E-mail :

commercial@tournus.cor

Export :

Tel : + 33 (0)3 85 27 42 65 E-mail : export@tournus.com


Site web :

- Stainless steel construction
- Colourless, transparent Plexiglas door with radiused corners, stainless steel hinges and magnetic fastening
- Sloped top and bottom, stop in lower part
- Device to switch off the U.V. tube when the doors are opened
- Protected electrical part: IP 24
- Timer adjustable from 0 to 2 hours, minimum recommended: 1h30 min
- 230 V electrical connection, power supply cord 1.2 m long

ref.806 421


87.5 4.00 87.5 Sansan - 575








ref.806 423









Nominal voltageFrequency230V 1N~50/60 Hz

- Input power : 15 W or 30 W depending on model

- Appliance classification : I
- Protection index : IP 24

- Standards : **NF EN 60335-1**

Description	Overall dim. I×W×h (mm)	Without key		With key	
		Ref.	Price	Ref.	Price
1 door, 25 knife capacity with grid in cut sheet metal	575 × 170 × 600	806 421	536 €	<u>816 421</u>	573 €
1 door, 15 knife capacity with magnetized bar	575 × 170 × 600	806 422	580 €	<u>816 422</u>	617 €
1 door, 25 knife capacity with stainless steel grid	575 × 170 × 600	806 423	626 €	<u>816 423</u>	663 €
2 doors, 50 knife capacity with stainless steel grid	1030×170×600	806 424	1030 €	816 424	1170 €