STAINLESS STEEL TABLES



TS 15N STAINLESS STEEL TABLES

Stainless steel tables, height 900 mm, adjustable up to 930 mm (850 mm tables available on request). Worktop thickness 1,5 mm, reinforced by 100% waterproof double-sided laminated board. Rounded worktop front and upstand. Underframe in (Ø 45 mm) stainless steel tube fitted with adjustable and non-slip feet. Fast assembly: no tools required. Rear legs recessed by 65 mm on tables with upstands and 55 mm on free-standing tables. Instant assembly of drawers in any position on the specially adapted frame. NF Hygiene Alimentaire.

Pedestal tables



Standard or made-tomeasure

Free-standing tables Free-standing tables + undershelf Tables with upstand Tables with upstand + undershelf

Tables on wheels







TS 15N CHEF'S TABLES

Worktop thickness 1,5 mm. Welded sink $400 \times 400 \times 250$ mm with overflow tube and siphon. Please consult us for chef's tables without upstand.

Chef's tables with tap



Standard or made-tomeasure

With upstand With upstand + under shelf

Chef's tables without tap



TS 15N WALL TABLES

Worktop thickness 1,5 mm. Fastening by 2 wall supports under upstand and 2 brakets Ø 45 mm with jacks for horizontal adjustment. Standard or made-to-measure (width 700 mm).

Stainless steel wall tables





Chef's wall tables without tap



SUPPLEMENTS FOR OTHER WIDTHS

To apply to the prices of custom-made tables width 700 mm.

OVERSHELVES FOR TABLES

Stainless steel construction. Cylindrical tubes Ø 32 mm. Adjustable shelves in brushed stainless steel, thickness 1,2 mm. Width 300 mm, height 400 mm (1 tier), 600 mm (2 tiers). Supplied with 2 fixing brackets.



WHEEL OPTIONS FOR STAINLESS STEEL TABLES

- Table with 4 swivel wheels ø 125 mm with polyamide cover and 2 brakes: 701 201
- Table with 4 swivel wheels ø 125 mm with stainless steel cover and 2 brakes: 701 204
- Semi-mobile table, 2 swivel wheels ø 125 mm with polyamide cover and 2 rear brakes: 701 203
- Semi-mobile table, 2 swivel wheels ø 125 mm with polyamide cover including 2 brakes + rear stop: 701 223
- Semi-mobile table, 2 s/steel swivel wheels ø 125 mm + rear stops: 701 224
- Semi-mobile table, 2 s/steel swivel wheels ø 125 mm including 2 brakes + rear stops: 701 225



CORNER SHELF

Shelf thickness 1,5 mm reinforced by laminated board with plated edges. Rounded upstand height 100 mm. Fastening by 2 wall supports under upstand and bolting to adjacent tables.



ACCESSORIES FOR S/STEEL TABLES


Drawers

- Drawer with front panel + GN 1/1 polypropylene: 809 561 (width 700 mm), 809 564 (adjustable width) and 819 564 (adjustable width + lock)
- Drawer with front panel + GN 1/1 copolyester: 849 561 (width 700 mm) and 849 564 (adjustable width)
- Drawer with front panel + GN 1/1 stainless steel: 829 561 (width 700 mm) and 829 564 (adjustable width)



Taps

- Mixer tap 1/2", flow rate 30 l/mn: 230 300
- Mixer tap chavonnet 5640 t3, flow rate 30 l/mn: 806 730
- Mixer tap with electronic control, flow rate 3 l/mn: 230 507
- 1 Water shower head: 230 240
 Mixer shower head: 507 545
- Mixer shower head + swan neck: 507 546
- Knee operated control for chef's table + disposal: 701 054
- Extra cost for brass trap: 272 110
- Cover basin cladding on 3 sides: 117 180
- Overflow tube and strainer: 806 688





Crosspieces

• 2 crosspieces for tables 600, 700 or 800 mm wide on legs or wheels

Hooked longitudinal

• Hooked longitudinal bar length 600 to 2400 mm can be hooked to braces

Others accessories

- Polyethylene sheet 600 × 600 mm on bases, placed on table: 801 953
- GN 1/1 sliding underframe 5 levels to fit under the frame of the table: 801 956
- 3 Drawers unit to fit under the frame table (width 600 and 700 mm): 801 959



EXTRAS TO BE ADDED TO THE PRICE OF CUSTOMIZED TABLES

Top

- Lateral right upstand 701 001 or left 701 002
- Cut side (allow 2 when tables with shelf): 701 003
- Notch for columns: 701 004Anti-drip edges: 701 005
- Orbital polishing, linear meter: 701 024
- Mirror polished edging, linear meter: 701 025

Extra-cost for worktop thickness 20/10 mm

- For tables length up to 1800 mm, linear meter : 701 008
- For tables length up to 1800 mm, linear meter: 701 009
- 2 Ball corners for upstand table: 701 080
- 4 Ball corners for central table: 701 079

Waste chute

- Waste chute with sloping sides ø 150 mm
- Waste chute with sloping sides ø 250 mm + rubber flange
- Rubber flange
- Stainless steel cover for waste chute ø 280 mm

Basins

- Welded basin 310 × 510 × 215 mm (GN 1/1)
- Welded basin 400 × 400 × 250 mm
- Welded basin 500 × 400 × 300 mm
- Welded basin 600 × 500 × 300 mm
- Cylindrical welded sink Ø 300 mm, prof. 160 mm

Risers for chef's tables

Riser for pan 500 × 600 mm : 806 931
 Riser for pan 600 × 600 mm : 806 932











EXTRA TO BE ADDED TO THE PRICE OF CUSTOMIZED TABLES

4 Rubber buffers: 701 2072 Rear bumpers: 701 206

• Stainless steel discharge tube on drain per pan: 701 110

Lateral upstand added to right: 701 012
Lateral upstand added to left: 701 013
Legs with stainless steel jack: 701 070

2 additional central feet for shorter lower shelf: 701 007

TABLES FOR OPENING TINS

For GN 1/1 containers. Welded stainless steel construction with covering on 3 sides, height 900 mm, depth 700 mm (tables on legs). Worktop thickness 1,5 mm, welded corners. Option: shower head.

Standard tables for opening tins:

- Legged table for 2, 3 or 4 pans
- Wall table for 2, 3 or 4 plans

Customized table on legs for opening tins



GARNISHING TABLE

Designed to facilitate the preparation of starters and salads. It means all the different ingredients can be kept close to hand for easy

and quick plating a large number of plates and small dishes, while limiting operations. Standard TS15N table, height 900 mm, top

1,5 mm thickness with fully sealed double sided laminate panel. Stainless steel tubular legs Ø 45 mm fitted with screw jacks with

runner stops at each end. GN stainless steel wire stand on wheels that can be moved alongside the table.



TABLES ON WHEELS

Welded stainless steel construction. 4 swivel wheels \emptyset 125 mm, with polyamide cover, including 2 brakes (except ref 801 305, wheels \emptyset 80 mm).

Table on wheels with shelf : $906\ 530\ (dim.\ 500\ x\ 800\ x\ 850\ mm)$, $801\ 300\ (dim.\ 670\ x\ 500\ x\ 750\ mm)$

Table on wheels: 801 305



APPLIANCE SUPPORT TABLES

Welded stainless steel construction. Square legs 35×35 mm with adjustable jacks 0/+25 mm. Plate 15/10th mm thick. Shelf 12/10th mm thick. Maximum weight: 150 kg. Table on wheels: wheels with polyamide cover Ø 125 mm including 2 with brakes.



STAINLESS STEEL WRITING DESKS

Stainless steel construction. Tilt worktop with folding cover forming inclined desk.

- Desk on legs
- Desk on wheels
- Wall desk



BASKET SUPPORT

- Structure for basket support length 1200 mm fixed to: 702 257
- Wall supports brackets for s/steel punnet basket (set of 2): 906 425
- Stainless steel basket for punnets: 906 830



GANTRY (BUTCHER)

Tube poles $60 \times 60 \times 3$ mm, upper cross bars of 120 mm. Flat latching bars of 80×10 spaced by 500 mm. Flat x-cross reinforcement bars of 40×6 mm. Load: 400 kg/m^2 . Height 2200 mm. Manufactured on request with drawing.



25 avenue Jean Moulin - CS2005 71700 TOURNUS - FRANCERC Mâcon B 383 567 104
Code APE 295 E
SAS Capital 16 355 625€

FRANCE Tél: 03 85 27 42 00

E-mail: commercial@tournus.com

EXPORT
Tél: + 33 (0)3 85 27 42 65
E-mail: export@tournus.com