

Standard units: Stainless steel construction. Reinforced worktop with water repellent laminate panel. Rounded front edge, 60 mm high. Cupboard with press-drawn base and radiused vertical edges. 3 levels of removable U-sliders provided on removable racks (easy tool-free dismantling). Adjustable sliders on 12 positions. Reversible doors with magnetic seal with return. Stainless steel tubular legs Ø 60 mm, height adjustable (-25/+25 mm). Voltage: 230V-1N. Regulator with built-in HACCP alarm: can store up to 3 alarms by saving the value of the critical temperature, date and time of alarm recording and alarm duration.

Refrigeration : Flush-mounted, fan-assisted evaporator with distribution tunnel in part of storage area, protected from splashes. The openings evenly distributed in the top guarantee even temperature distribution. Injection moulded polyurethane insulation 50 mm thick in base, top, rear, sides and doors. Operation designed for an ambient temperature up to 43°C. Coolant gas R290. Electronic thermostat with digital readout. Automatic defrosting with evaporation tray for condensation water. Removable compressor. Programmable display for compressor servicing.

Units without compressor : Supplied with evaporator, control and regulator. Technical compartment for connections.

GN refrigerated units with compressor

GN 1/1 refrigerated units, opening 325 mm, height 900 mm



POSITIVE REFRIGERATION
 (- 2°C + 10°C)



508 011



508 012

Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 DOOR	700 x 859	598	508 001	528 001
2 drawers, height 210 mm	700 x 859	598	508 002	528 002
3 drawers, height 105 mm	700 x 859	598	508 004	528 004
2 drawers height 320 + 105 mm	700 x 859	598	508 005	528 005
2 DOORS	700 x 1313	698	508 011	528 011
1 door + 2 drawers, h. 210 mm	700 x 1313	698	508 012	528 012
2 x 2 drawers, height 210 mm	700 x 1313	698	508 013	528 013
1 door + 3 drawers, h. 105 mm	700 x 1313	698	508 014	528 014
1 door + 2 drawers h. 320 + 105 mm	700 x 1313	698	508 015	528 015
3 DOORS	700 x 1767	1000	508 021	528 021
2 doors + 2 drawers h. 210 mm	700 x 1767	1000	508 022	528 022
1 door + 2 x 2 drawers h. 210 mm	700 x 1767	1000	508 023	528 023
2 doors + 3 drawers h. 105 mm	700 x 1767	1000	508 024	528 024
2 doors + 2 drawers h. 320 + 105 mm	700 x 1767	1000	508 025	528 025
4 DOORS	700 x 2221	1170	508 031	528 031
3 doors + 2 drawers h. 210 mm	700 x 2221	1170	508 032	528 032
2 doors + 2 x 2 drawers h. 210 mm	700 x 2221	1170	508 033	528 033
3 doors + 3 drawers h. 105 mm	700 x 2221	1170	508 034	528 034
3 doors + 2 drawers h. 320 + 105 mm	700 x 2221	1170	508 035	528 035

GN refrigerated unit with compressor

GN 1/1 refrigerated units, opening 325 mm, height 900 mm



NEGATIVE REFRIGERATION
(- 20°C - 10°C)



528 048

Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 door	700 × 859	577	508 046	528 046
2 doors	700 × 1313	834	508 047	528 047
3 doors	700 × 1767	1061	508 048	528 048

GN refrigerated units without compressor

GN 1/1 refrigerated units, opening 325 mm, height 900 mm



POSITIVE REFRIGERATION
(- 2°C + 10°C)



528 111

Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 DOOR				
2 drawers, height 210 mm	700 × 669	598	508 101	528 101
3 drawers, height 105 mm	700 × 669	598	508 102	528 102
2 drawers, height 320 + 105 mm	700 × 669	598	508 104	528 104
2 drawers, height 320 + 105 mm	700 × 669	598	508 105	528 105
2 DOORS				
1 door + 2 drawers h. 210 mm	700 × 1123	698	508 111	528 111
2 x 2 drawers h. 210 mm	700 × 1123	698	508 112	528 112
2 x 2 drawers h. 210 mm	700 × 1123	698	508 113	528 113
1 door + 3 drawers h. 105 mm	700 × 1123	698	508 114	528 114
2 doors + 2 drawers h. 320 + 105 mm	700 × 1123	698	508 115	528 115
3 DOORS				
2 doors + 2 drawers, h. 210 mm	700 × 1577	1000	508 121	528 121
2 doors + 2 drawers, h. 210 mm	700 × 1577	1000	508 122	528 122
1 door + 2 x 2 drawers h. 210 mm	700 × 1577	1000	508 123	528 123
2 doors + 3 drawers h. 105 mm	700 × 1577	1000	508 124	528 124
2 doors + 2 drawers h. 320 + 105 mm	700 × 1577	1000	508 125	528 125
4 DOORS				
3 doors + 2 drawers h. 210 mm	700 × 2031	1170	508 131	528 131
3 doors + 2 drawers h. 210 mm	700 × 2031	1170	508 132	528 132
2 doors + 2 x 2 drawers h. 210 mm	700 × 2031	1170	508 133	528 133
3 doors + 3 drawers h. 105 mm	700 × 2031	1170	508 134	528 134
3 doors + 2 drawers h. 320 + 105 mm	700 × 2031	1170	508 135	528 135



528 122

GN refrigerated unit without compressor

GN 1/1 refrigerated units, opening 325 mm, height 900 mm



NEGATIVE REFRIGERATION
(- 20°C - 10°C)

Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 door	700 × 669	577	508 146	528 146
2 doors	700 × 1123	834	508 147	528 147
3 doors	700 × 1577	1061	508 148	528 148

25 avenue Jean Moulin - CS2005
71700 TOURNUS - FRANCE
RC Mâcon B 383 567 104
Code APE 295 E
SAS Capital 16 355 625€

FRANCE
Tel : 03 85 27 42 42
E-mail : commercial@tournus.com

EXPORT
Tel : + 33 (0)3 85 27 42 65
E-mail : export@tournus.com

Euronorm refrigerated units with compressor

Euronorm refrigerated units, opening 400 mm, height 900 mm



508 202

Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 door	800 × 934	596	508 201	528 201
2 doors	800 × 1463	825	508 202	528 202
3 doors	800 × 1992	1000	508 203	528 203
4 doors	800 × 2521	1170	508 204	528 204

Euronorm refrigerated units with compressor

Euronorm refrigerated units, opening 400 mm, height 900 mm



Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 door	800 × 934	580	508 216	528 216
2 doors	800 × 1463	834	508 217	528 217
3 doors	800 × 1992	910	508 218	528 218

Euronorm refrigerated units without compressor

Euronorm refrigerated, opening 400 mm, height 900 mm



Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 door	800 × 744	596	508 231	528 231
2 doors	800 × 1273	825	508 232	528 232
3 doors	800 × 1802	1000	508 233	528 233
4 doors	800 × 2331	1170	508 234	528 234

Euronorm refrigerated units without compressor

Euronorm refrigerated, opening 400 mm, height 900 mm



528 247

Units with	Overall dim. W x l (mm)	Power (W)	Without upstand Ref.	With upstand Ref.
1 door	800 × 744	580	508 246	528 246
2 doors	800 × 1273	834	508 247	528 247
3 doors	800 × 1802	910	508 248	528 248

Extra charges for refrigerated units

Description	Reference
Granit top, 30 mm thick, per m ²	701 760
Usb plug	701 622
2 Extra sliders (1 level, extra per door)	701 627
4 wheels with stainless steel cover, 2 with brakes	701 628

25 avenue Jean Moulin - CS2005
71700 TOURNUS - FRANCE
RC Mâcon B 383 567 104
Code APE 295 E
SAS Capital 16 355 625€

FRANCE
Tel : 03 85 27 42 42
E-mail : commercial@tournus.com

EXPORT
Tel : + 33 (0)3 85 27 42 65
E-mail : export@tournus.com