



805 704

## Racking units with s/steel tubes

Stainless steel welded construction. Height 1800 mm. Uprights made 30 x 30 mm. 4 shelves in tubes 25 x 25 mm. Load : 200 kg per level (with a maximum of 400 kg for all the wheels).

Racking units include 4 adjustable feet, racking units on wheels are equipped with 4 wheels ø 125 mm including 2 with brakes.

Description	Overall dim. W x l (mm)	Racking units on legs	Racking units on wheels
Racking units, 4 levels	600 x 1000	<a href="#">805 704</a>	<a href="#">825 704</a>
Racking units, 4 levels	600 x 1400	<a href="#">805 705</a>	<a href="#">825 705</a>
Racking units, 4 levels	600 x 1800	<a href="#">805 706</a>	<a href="#">825 706</a>

## Racking units with aluminium shelves

Racking units made in anodised aluminium. Easy assembly by tapered self-locking insertion without tools. Load: up to 150 kg per level.

Certification NF-Hygiène Alimentaire



ALH 1192

Description	Overall dim. W. x l (mm)	Reference
Racking unit 3 levels	560 x 1200	<a href="#">ALG 1192</a>
Racking unit 4 levels	560 x 1200	<a href="#">ALH 1192</a>
Racking unit 3 levels	560 x 1500	<a href="#">ALG 1494</a>
Racking unit 4 levels	560 x 1500	<a href="#">ALH 1494</a>

